

## \* SECURI-WALL



## PRECISION ENGINEERING FROM GROUND TO SKY

The SECURI-WALL foundation is designed to be mostly below ground, so an excavation is required and ground-compacted to Echo and Topfloor's specification. Then a hollow-core slab is used as a solid base, which is completely level. This is imperative for the overall aesthetic appearance. Practically, the wall is 3.6m high; 3.0m above ground and 600mm below ground. We can vary the height according to the client's requirements. The installation is done by mobile crane. Both the SECURI-WALL column and the hollow-core slab are delivered on 25-ton trucks and installed by mobile crane. The site condition and reach from where the mobile crane will stand determines the size of crane required.







Sara (KZN): 083 601 7284 Ahmed (W. Cape): 078 555 1515 Brigitte (W. Cape): 071 305 3115

securi-wall.co.za





## \* SECURI-WALL



## PRECISION ENGINEERING FROM GROUND TO SKY

The SECURI-WALL foundation is designed to be mostly below ground, so an excavation is required and ground-compacted to Echo and Topfloor's specification. Then a hollow-core slab is used as a solid base, which is completely level. This is imperative for the overall aesthetic appearance. Practically, the wall is 3.6m high; 3.0m above ground and 600mm below ground. We can vary the height according to the client's requirements. The installation is done by mobile crane. Both the SECURI-WALL column and the hollow-core slab are delivered on 25-ton trucks and installed by mobile crane. The site condition and reach from where the mobile crane will stand determines the size of crane required.







Adele: 067 088 8527 Anzelle: 082 760 2167

securi-wall.co.za

